



## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : SPM NON CRISTALLISANT

Product code : 12045/12046/24281.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Abrasive for polishing or lapping

#### 1.3. Details of the supplier of the safety data sheet

Registered company name : PRESI S.A.

Address : 11 Rue du vercors.38320.EYBENS.France.

Telephone : +33 (0)4.76.72.00.21. Fax : +33 (0)4.76.72.05.84.

presi@presi.com

www.presi.com

#### 1.4. Emergency telephone number : +33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

### SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### In compliance with EC regulation No. 1272/2008 and its amendments.

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

#### 2.2. Label elements

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :

EUH208 Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Hazard statements :

#### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European CHemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

### SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

##### Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 7631-86-9 EC: 231-545-4  SILICON DIOXIDE		[1]	25 <= x % < 50
CAS: 107-21-1 EC: 203-473-3 REACH: 01-2119456816-28  ETHYLENE GLYCOL	GHS07, GHS08 Wng Acute Tox. 4, H302 STOT RE 2, H373	[1]	2.5 <= x % < 10



**SPM NON CRISTALLISANT - 12045/12046/24281**

INDEX: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9  1,2-BENZISOTHIAZOL-3(2H)-ONE	GHS05, GHS07, GHS09 Dgr Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 M Acute = 1		0 ≤ x % < 1
--	---	--	-------------

(Full text of H-phrases: see section 16)

**Information on ingredients :**

[1] Substance for which maximum workplace exposure limits are available.

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures**

**In the event of exposure by inhalation :**

In the event of an allergic reaction, seek medical attention.

Move to fresh air

**In the event of splashes or contact with eyes :**

Rinse immediately with plenty of water, also under the eyelids

Consult a physician if necessary

**In the event of splashes or contact with skin :**

In the event of an allergic reaction, seek medical attention.

Take off all contaminated clothing immediately

Wash off immediately with soap and plenty of water

**In the event of swallowing :**

Seek medical attention, showing the label.

Do not induce vomiting without medical advice

Rinse mouth thoroughly with water

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

**SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

**5.1. Extinguishing media**

**Suitable methods of extinction**

Water, foam, sand, powder or CO<sub>2</sub>, according to the surrounding materials

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

In the event of fire, wear self-contained breathing apparatus



**SPM NON CRISTALLISANT - 12045/12046/24281**

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

**Fire prevention :**

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

Store between 5°C and 40°C

Keep the container tightly closed in a cool, well ventilated place

**Storage**

Keep in a cool dry place

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**Occupational exposure limits :**

- European Union (2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
107-21-1	52	20	104	40	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-21-1	-	-	100	-	-

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

CAS	VME :	VME :	Excess	Notes

**SPM NON CRISTALLISANT - 12045/12046/24281**

7631-86-9		4 E mg/m <sup>3</sup>		
107-21-1		10 ppm 26 mg/m <sup>3</sup>		2(I)

- Canada / Ontario (Control of exposure to biological or chemical agents, regulation 491/2009) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-21-1	-	-	100 mg/m <sup>3</sup>	-	-

- Canada / Quebec (Regulations on occupational health and safety) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-21-1			50 ppm 127 mgm/3	RP	

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m <sup>3</sup> :	VLE-ppm :	VLE-mg/m <sup>3</sup> :	Notes :	TMP No :
107-21-1	20	52	40	104	*	84

- Japan (JSOH, 11/05/2017) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
7631-86-9	4 mg/m <sup>3</sup>				

- Switzerland (SUVAPRO 2017) :

CAS	VME	VLE	Valeur plafond	Notations
7631-86-9				SSC
107-21-1	10 ppm 26 mg/m <sup>3</sup>	20 ppm 52 mg/m <sup>3</sup>		R SSC

- USA / NIOSH IDLH (National Institute for Occupational Safety and Health, Immediately Dangerous to Life or Health Concentrations) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
7631-86-9	6 mg/m <sup>3</sup>				

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-21-1	20 ppm 52 mg/m <sup>3</sup>	40 ppm 104 mg/m <sup>3</sup>			

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

ETHYLENE GLYCOL (CAS: 107-21-1)

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Dermal contact.  
Long term systemic effects.  
106 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term local effects.  
35 mg of substance/m<sup>3</sup>

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Consumers.**

Dermal contact.  
Long term systemic effects.  
53 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term local effects.  
7 mg of substance/m<sup>3</sup>

**Predicted no effect concentration (PNEC):**

ETHYLENE GLYCOL (CAS: 107-21-1)

Environmental compartment:

Soil.

**SPM NON CRISTALLISANT - 12045/12046/24281**

PNEC :	1.53 mg/kg
Environmental compartment: PNEC :	Fresh water. 10 mg/l
Environmental compartment: PNEC :	Sea water. 1 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 10 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 37 mg/kg
Environmental compartment: PNEC :	Marine sediment. 3.7 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 199.5 mg/l

## 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

#### - Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

#### - Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.



**SPM NON CRISTALLISANT - 12045/12046/24281**

---

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**General information :**

Physical state : Fluid liquid.

**Important health, safety and environmental information**

pH : Not stated.  
Slightly basic.

pH (aqueous solution) : 9-11

Boiling point/boiling range : 100°C

Flash point interval : Not relevant.

Vapour pressure (50°C) : Not relevant.

Density : 1050-1400

Water solubility : Dilutable.

Viscosity : < 50 mPa.s à 20°C

Melting point/melting range : 0°C

Self-ignition temperature : Not specified.

Decomposition point/decomposition range : Not specified.

**9.2. Other information**

No data available.

---

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Avoid :

- frost

**10.5. Incompatible materials**

Keep away from :

- aluminium

Zinc

Mild steel

**10.6. Hazardous decomposition products**

No data available.

---

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

No data available.

**11.1.1. Substances**

**Acute toxicity :**

ETHYLENE GLYCOL (CAS: 107-21-1)

Oral route :

LD50 = 2000 mg/kg

Species : Rat



**SPM NON CRISTALLISANT - 12045/12046/24281**

---

Dermal route : LD50 > 3500 mg/kg  
Species : Mouse

**Respiratory or skin sensitisation :**

ETHYLENE GLYCOL (CAS: 107-21-1)  
Local lymph node stimulation test : Non-Sensitiser.

**Germ cell mutagenicity :**

ETHYLENE GLYCOL (CAS: 107-21-1)  
Mutagenesis (in vivo) : Negative.  
Species : Rat

Ames test (in vitro) : Negative.  
Species : S. typhimurium TA102

**11.1.2. Mixture**

**Acute toxicity :**

Species : Rat  
LD50 > 5000 mg/kg

**Respiratory or skin sensitisation :**

Contains at least one sensitising substance. May cause an allergic reaction.

Local lymph node stimulation test : Non-sensitiser.  
OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity :**

Ames test (in vitro) : Negative.  
OCDE 471 (Reverse mutation test bacteria).

**Carcinogenicity :**

No carcinogenic effect.

---

**SECTION 12 : ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.1.1. Substances**

ETHYLENE GLYCOL (CAS: 107-21-1)  
Fish toxicity : LC50 = 72860 mg/l  
Species : Pimephales promelas  
Duration of exposure : 96 h

NOEC = 15830 mg/l  
Species : Pimephales promelas  
Duration of exposure : 7 days

Crustacean toxicity : EC50 > 100 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h  
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity : ECr50 > 100 mg/l  
Species : Pseudokirchnerella subcapitata



**SPM NON CRISTALLISANT - 12045/12046/24281**

---

Duration of exposure : 96 h

**12.1.2. Mixtures**

LC50 > 5000 mg/l  
Duration of exposure : 96 h  
EC50 = 7600 mg/l  
Duration of exposure : 48 h  
ECr50 = 120 mg/l  
Duration of exposure : 48 h  
NOEC = 60 mg/l  
Species : Selenastrum capricornutum  
Duration of exposure : 48 h  
EC10 = 140 mg/l  
Species : Selenastrum capricornutum  
Duration of exposure : 48 h

**12.2. Persistence and degradability**

**12.2.1. Substances**

ETHYLENE GLYCOL (CAS: 107-21-1)

Biodegradability : Rapidly degradable.

**12.3. Bioaccumulative potential**

**12.3.1. Substances**

ETHYLENE GLYCOL (CAS: 107-21-1)

Bioaccumulation : BCF < 100

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

No data available.

**German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 1 : Slightly hazardous for water.

---

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.



#### **SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

**14.1. UN number**

-

**14.2. UN proper shipping name**

-

**14.3. Transport hazard class(es)**

-

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

-

---

#### **SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/669 (ATP 11)

**- Container information:**

No data available.

**- Particular provisions :**

No data available.

**- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 1 : Slightly hazardous for water.

**15.2. Chemical safety assessment**

No data available.

---

#### **SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.

**Abbreviations :**

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.



---

**SPM NON CRISTALLISANT - 12045/12046/24281**

---

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.