



## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : RESINE KM-V LIQUIDE  
Product code : 04033/04035.  
LIQUID RESIN KM-V / HÄRTER KM-V  
KIT : 04031

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Resin coating

#### 1.3. Details of the supplier of the safety data sheet

Registered company name : PRESI S.A.  
Address : 11 Rue du vercors.38320.EYBENS.France.  
Telephone : +33 (0)4.76.72.00.21. Fax : +33 (0)4.76.72.05.84.  
presi@presi.com  
www.presi.com

#### 1.4. Emergency telephone number : +33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

### SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

#### 2.2. Label elements

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02



GHS07

Signal Word :

DANGER

Product identifiers :

EC 201-297-1

METHYL METHACRYLATE

EC 203-652-6

2,2'-ETHYLENEDIOXYDIETHYL DIMETHACRYLATE

Hazard statements :

H225

Highly flammable liquid and vapour.

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

H319

Causes serious eye irritation.

H335

May cause respiratory irritation.

**RESINE KM-V LIQUIDE - 04033/04035**

Precautionary statements - Prevention :

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P243 Take action to prevent static discharges.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312 Call a POISON CENTER/doctor/... if you feel unwell.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P337 + P313 If eye irritation persists: Get medical advice/attention.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.

Precautionary statements - Storage :

- P403 + P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.

**2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2. Mixtures**

**Composition :**

Identification	(EC) 1272/2008	Note	%
CAS: 80-62-6 EC: 201-297-1 REACH: 01-2119452498-28 METHYL METHACRYLATE	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335	D [1]	25 $\leq$ x % < 50
CAS: 109-16-0 EC: 203-652-6 2,2'-ETHYLENEDIOXYDIETHYL DIMETHACRYLATE	GHS07 Wng Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 STOT SE 3, H335		25 $\leq$ x % < 50
CAS: 99-97-8 EC: 202-805-4 N,N-DIMETHYL-P-TOLUIDINE	GHS06, GHS08 Dgr Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT RE 2, H373 Aquatic Chronic 3, H412	C	2.5 $\leq$ x % < 10

(Full text of H-phrases: see section 16)

**Information on ingredients :**

[1] Substance for which maximum workplace exposure limits are available.



**RESINE KM-V LIQUIDE - 04033/04035**

---

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures**

**In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

If symptoms persist, call a physician

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

**In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

If the event contact with skin : Wash immediatly and abundantly with poly-ethyleneglycol then with a lot of water

**In the event of swallowing :**

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. contact a physician.

---

**SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

**5.1. Extinguishing media**

Keep packages near the fire cool, to prevent pressurised containers from bursting.

**Suitable methods of extinction**

In the event of a fire, use :

- carbon dioxide (CO<sub>2</sub>)

- foam

- powder

Prevent the effluent of fire-fighting measures from entering drains or waterways.

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)



**RESINE KM-V LIQUIDE - 04033/04035**

**5.3. Advice for firefighters**

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Safe handling advice

Avoid contact with skin and eyes

**Fire prevention :**

Handle in well-ventilated areas.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**RESINE KM-V LIQUIDE - 04033/04035**

**7.2. Conditions for safe storage, including any incompatibilities**

- Keep away from food, drink and animals feeding stuffs
- Do not smoke
- Stock between 15°C and 25°C
- Keep only in the original container

**Storage**

- Keep the container tightly closed in a dry, well-ventilated place.
- Keep away from all sources of ignition - do not smoke.
- Keep well away from all sources of ignition, heat and direct sunlight.
- Avoid accumulation of electrostatic charges.
- Don't store with : oxidizing agents, pyrophoric and self-heating substances

**Packaging**

- Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

- No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**Occupational exposure limits :**

- European Union (2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3	VME-ppm	VLE-mg/m3	VLE-ppm	Notes
80-62-6	-	50	-	100	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
80-62-6	50 ppm	100 ppm		SEN; A4	

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

CAS	VME :	VME :	Excess	Notes
80-62-6		50 ppm 210 mg/m <sup>3</sup>		2(I)

- Canada / Ontario (Control of exposure to biological or chemical agents, regulation 491/2009) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
80-62-6	50 ppm	100 ppm	-	-	-

- Canada / Quebec (Regulations on occupational health and safety) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
80-62-6	50 ppm 205 mg/m <sup>3</sup>			S	

- France (INRS - ED984 :2016) :

CAS	VME-ppm	VME-mg/m3	VLE-ppm	VLE-mg/m3	Notes	TMP No :
80-62-6	50	205	100	410	-	82

- Japan (JSOH, 11/05/2017) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
80-62-6	8,3 mg/m <sup>3</sup>				

- Switzerland (SUVAPRO 2017) :

CAS	VME	VLE	Valeur plafond	Notations
80-62-6	50 ppm 210 mg/m <sup>3</sup>	100 ppm 420 mg/m <sup>3</sup>		S SSC

- USA / NIOSH IDLH (National Institute for Occupational Safety and Health, Immediately Dangerous to Life or Health Concentrations) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
80-62-6	100 ppm 410 mg/m <sup>3</sup>				

**RESINE KM-V LIQUIDE - 04033/04035**

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
80-62-6	50 ppm 208 mg/m <sup>3</sup>	100 ppm 416 mg/m <sup>3</sup>			

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

METHYL METHACRYLATE (CAS: 80-62-6)

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Dermal contact.  
Long term systemic effects.  
17 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
208 mg of substance/m<sup>3</sup>

**Predicted no effect concentration (PNEC):**

METHYL METHACRYLATE (CAS: 80-62-6)

Environmental compartment:  
PNEC :

Fresh water.  
0.94 mg/l

**8.2. Exposure controls**

**Appropriate engineering controls**

Avoid contact with skin, eyes and clothing

**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

**- Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Recommended properties :

- Impervious gloves in accordance with standard EN374

**- Body protection**

Avoid skin contact.

Wear suitable protective clothing.



**RESINE KM-V LIQUIDE - 04033/04035**

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

To envisage normal working clothes

**- Respiratory protection**

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

---

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**General information :**

Physical state : Fluid liquid.

**Important health, safety and environmental information**

pH :	Not relevant.
Boiling point/boiling range :	100.5°C
Flash Point :	10.00 °C.
Explosive properties, lower explosivity limit (%) :	2.1
Explosive properties, upper explosivity limit (%) :	12.5
Vapour pressure (50°C) :	Not relevant.
Vapour density :	3.5 (à 20°C)
Density :	0.949 g/cm <sup>3</sup> (à 15°C)
Water solubility :	Insoluble. 12.5 g/L (à 20°C)
Partition coefficient: n-octanol/water :	1.38
Viscosity :	0.53 mPa.s (à 20°C)
Melting point/melting range :	-48°C
Self-ignition temperature :	Not specified.
Decomposition point/decomposition range :	Not specified.

**9.2. Other information**

No data available.

---

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

Fire risk

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.



**RESINE KM-V LIQUIDE - 04033/04035**

- heating
- heat
- flames and hot surfaces

**10.5. Incompatible materials**

Keep away from :  
pyrophoric and self-heating substances  
Incompatible with oxidising agents  
Strong acids and bases

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :  
- carbon monoxide (CO)  
- carbon dioxide (CO<sub>2</sub>)

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.

May cause an allergic reaction by skin contact.

**11.1.1. Substances**

**Acute toxicity :**

N,N-DIMETHYL-P-TOLUIDINE (CAS: 99-97-8)

Oral route :	LD50 = 100 mg/kg
Dermal route :	LD50 = 300 mg/kg
Inhalation route (n/a) :	LC50 = 1.4 mg/l Species : Rat Duration of exposure : 4 h

2,2'-ETHYLENEDIOXYDIETHYL DIMETHACRYLATE (CAS: 109-16-0)

Oral route :	LD50 > 5000 mg/kg Species : Rat
--------------	------------------------------------

METHYL METHACRYLATE (CAS: 80-62-6)

Oral route :	LD50 > 5000 mg/kg Species : Rat OECD Guideline 401 (Acute Oral Toxicity)
--------------	--

Dermal route :	LD50 > 5000 mg/kg Species : Rabbit
----------------	---------------------------------------

Inhalation route (n/a) :	LC50 = 29.8 mg/l Species : Rat Duration of exposure : 4 h
--------------------------	---

**Skin corrosion/skin irritation :**

Irritating to skin

**Serious damage to eyes/eye irritation :**

Irritating to eyes





**RESINE KM-V LIQUIDE - 04033/04035**

**11.1.2. Mixture**

**Acute toxicity :**

Oral route : No observed effect.  
Species : Rat  
LD50 = 7870 mg/kg

Dermal route : No observed effect.  
Species : Rabbit  
LD50 > 5000 mg/kg  
LC50 = 78 mg/l

**Respiratory or skin sensitisation :**

Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons

**SECTION 12 : ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.1.1. Substances**

N,N-DIMETHYL-P-TOLUIDINE (CAS: 99-97-8)

Fish toxicity : LC50 = 52 mg/l  
Species : Oncorhynchus mykiss  
Duration of exposure : 96 h

2,2'-ETHYLENEDIOXYDIETHYL DIMETHACRYLATE (CAS: 109-16-0)

Fish toxicity : LC50 = 16.4 mg/l  
Species : Brachydanio rerio  
Duration of exposure : 96 h

METHYL METHACRYLATE (CAS: 80-62-6)

Fish toxicity : LC50 > 79 mg/l  
Species : Oncorhynchus mykiss  
Duration of exposure : 96 h  
OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity :

EC50 69 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h  
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

NOEC = 37 mg/l  
Species : Daphnia magna  
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity :

ECr50 > 110 mg/l  
Species : Selenastrum capricornutum  
Duration of exposure : 72 h  
OECD Guideline 201 (Alga, Growth Inhibition Test)

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability**

Inherently biodegradable



**RESINE KM-V LIQUIDE - 04033/04035**

---

**12.2.1. Substances**

N,N-DIMETHYL-P-TOLUIDINE (CAS: 99-97-8)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

2,2'-ETHYLENEDIOXYDIETHYL DIMETHACRYLATE (CAS: 109-16-0)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

METHYL METHACRYLATE (CAS: 80-62-6)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

**12.3. Bioaccumulative potential**

Environmental long term harmful effects are not probable

**12.3.1. Substances**

N,N-DIMETHYL-P-TOLUIDINE (CAS: 99-97-8)

Octanol/water partition coefficient : log K<sub>ow</sub> = 2.81

METHYL METHACRYLATE (CAS: 80-62-6)

Octanol/water partition coefficient : log K<sub>ow</sub> = 1.38

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

No data available.

**German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 3 : Extremely hazardous for water.

---

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

---

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

**14.1. UN number**

1247

**14.2. UN proper shipping name**

UN1247=METHYL METHACRYLATE MONOMER, STABILIZED

**RESINE KM-V LIQUIDE - 04033/04035**

**14.3. Transport hazard class(es)**

- Classification :



3

**14.4. Packing group**

II

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	II	3	339	1 L	386	E2	2	D/E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	3	-	II	1 L	F-E,S-D	386	E2

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	II	353	5 L	364	60 L	A209	E2
	3	-	II	Y341	1 L	-	-	A209	E2

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available.

**SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/669 (ATP 11)

**- Container information:**

No data available.

**- Particular provisions :**

No data available.

**- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 3 : Extremely hazardous for water.

**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H225 Highly flammable liquid and vapour.  
H301 Toxic if swallowed.



**RESINE KM-V LIQUIDE - 04033/04035**

---

H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure .
H412	Harmful to aquatic life with long lasting effects.

**Abbreviations :**

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.