



SUSPENSION DIAMANTEE DE/SY - 09009/09016

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SUSPENSION DIAMANTEE DE/SY
Product code : 09009/09016.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Diamonds suspension for polishing or grinding

1.3. Details of the supplier of the safety data sheet

Registered company name : PRESI S.A.S.
Address : 11 Rue du vercors.38320.EYBENS.France.
Telephone : +33 (0)4.76.72.00.21. Fax : +33 (0)4.76.72.05.84.
presi@presi.com
www.presi.com

1.4. Emergency telephone number : +33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02

Signal Word :

WARNING

Hazard statements :

H226 Flammable liquid and vapour.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/...]equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Precautionary statements - Storage :

P403 + P235 Store in a well-ventilated place. Keep cool.

SUSPENSION DIAMANTEE DE/SY - 09009/09016

Precautionary statements - Disposal :

P501 Dispose of contents/container to ...

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 603-002-00-5 CAS: 64-17-5 EC: 200-578-6 REACH: 01-2119457610-43-0000 ETHANOL	GHS02 Dgr Flam. Liq. 2, H225	[1]	25 \leq x % < 50
CAS: 57-55-6 EC: 200-338-0 REACH: 01-2119456809-23 PROPYLENE GLYCOL		[1]	2.5 \leq x % < 10
CAS: 111-76-2 EC: 203-905-0 REACH: 01-2119475108-36 2-BUTOXYETHANOL	GHS07 Wng Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332	[1]	2.5 \leq x % < 10
CAS: 25322-68-3 EC: 500-038-2 POLYETHYLENEGLYCOL		[1]	1 \leq x % < 2.5
CAS: 25322-68-3 EC: 500-038-2 POLYETHYLENEGLYCOL (PEG-6)		[1]	1 \leq x % < 2.5
CAS: 25322-68-3 EC: 500-038-2 POLYETHYLENEGLYCOL		[1]	1 \leq x % < 2.5
CAS: 78-93-3 EC: 201-159-0 REACH: 01-2119457290-43-0000 BUTANONE	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH:066	[1]	0 \leq x % < 1
INDEX: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 REACH: 01-2119457558-25-XXXX PROPAN-2-OL	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]	0 \leq x % < 1

(Full text of H-phrases: see section 16)

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.



SUSPENSION DIAMANTEE DE/SY - 09009/09016

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of swallowing :

Seek medical attention, showing the label.

Do not induce vomiting without medical advice

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Water, foam, sand, powder or CO₂, according to the surrounding materials

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

Cleaning with water

6.4. Reference to other sections

No data available.



SUSPENSION DIAMANTEE DE/SY - 09009/09016

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Fire prevention :

Handle in well-ventilated areas.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically non-conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Stock between 15°C and 25°C

Keep the container tightly closed in a cool, well ventilated place

Keep the container away from dampness

Do not smoke

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m ³ :	VME-ppm :	VLE-mg/m ³ :	VLE-ppm :	Notes :
111-76-2	98	20	246	50	Peau
78-93-3	600	200	900	300	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5		1000 ppm		A3	
111-76-2	20 ppm			A3; BEI	
78-93-3	200 ppm	300 ppm		BEI	
67-63-0	200 ppm	400 ppm		A4; BEI	

SUSPENSION DIAMANTEE DE/SY - 09009/09016

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

CAS	VME :	VME :	Excess	Notes
64-17-5		500 ppm 960 mg/m ³		2(II)
111-76-2		10 ppm 49 mg/m ³		4(II)
78-93-3		200 ppm 600 mg/m ³		1(I)
67-63-0		200 ppm 500 mg/m ³		2(II)

- Canada / Ontario (Control of exposure to biological or chemical agents, regulation 491/2009) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
57-55-6	50 (V) ppm 155 mg/m ³				
111-76-2	20 ppm	-	-	-	-
67-63-0	200 ppm	400 ppm	-	-	-

- Canada / Quebec (Regulations on occupational health and safety) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm 1880 mg/m ³				
111-76-2	20 ppm 97 mg/m ³				
78-93-3	50 ppm 150 mg/m ³	100 ppm 300 mg/m ³			
67-63-0	400 ppm 983 mg/m ³	500 ppm 1230 mg/m ³			

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m ³ :	VLE-ppm :	VLE-mg/m ³ :	Notes :	TMP No :
64-17-5	1000	1900	5000	9500	-	84
111-76-2	10	49	50	246	*	84
78-93-3	200	600	300	900	*	84
67-63-0	-	-	400	980	-	84

- Japan (JSOH, 11/05/2017) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
111-76-2			20 ppm 97 mgm ³		
78-93-3	200 ppm 590 mg/m ³				
67-63-0			400 ppm 980 mgm ³		

- Switzerland (SUVAPRO 2017) :

CAS	VME	VLE	Valeur plafond	Notations
64-17-5	500 ppm 960 mg/m ³	1000 ppm 1920 mg/m ³		SSC
111-76-2	10 ppm 49 mg/m ³	20 ppm 98 mg/m ³		R B SSC
25322-68-3	1000 mg/m ³			SSC
25322-68-3	1000 mg/m ³			SSC
25322-68-3	1000 mg/m ³			SSC
78-93-3	200 ppm 590 mg/m ³	200 ppm 590 mg/m ³		R B SSC
67-63-0	200 ppm 500 mg/m ³	400 ppm 1000 mg/m ³		B SSC

SUSPENSION DIAMANTEE DE/SY - 09009/09016

- USA / NIOSH IDLH (National Institute for Occupational Safety and Health, Immediately Dangerous to Life or Health Concentrations) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	-	-	3300	-	-
111-76-2	5 ppm 24 mg/m ³			skin	
78-93-3	200 ppm 590 mg/m ³	300 ppm 885 mg/m ³			
67-63-0	400 ppm 980 mg/m ³	500 ppm 1225 mg/m ³			

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm 1920 mg/m ³	- ppm - mg/m ³			
57-55-6	150 ppm 474 mg/m ³	- ppm - mg/m ³			
111-76-2	25 ppm 123 mg/m ³	50 ppm 246 mg/m ³		Sk, BMGV	
78-93-3	200 ppm 600 mg/m ³	300 ppm 899 mg/m ³		Sk, BMGV	
67-63-0	400 ppm 999 mg/m ³	500 ppm 1250 mg/m ³			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

PROPAN-2-OL (CAS: 67-63-0)

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
888 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
500 mg of substance/m³

Final use:

Exposure method:
Potential health effects:
DNEL :

Consumers.

Ingestion.
Long term systemic effects.
26 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Dermal contact.
Long term systemic effects.
319 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
89 mg of substance/m³

BUTANONE (CAS: 78-93-3)

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
1161 mg/kg body weight/day

Exposure method:
Potential health effects:

Inhalation.
Long term systemic effects.



SUSPENSION DIAMANTEE DE/SY - 09009/09016

DNEL : 600 mg of substance/m³

Final use:

Man exposed via the environment.

Exposure method:
Potential health effects:
DNEL :

Ingestion.
Long term systemic effects.
31 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Dermal contact.
Long term systemic effects.
412 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
106 mg of substance/m³

2-BUTOXYETHANOL (CAS: 111-76-2)

Final use:

Workers.

Exposure method:
Potential health effects:
DNEL :

Dermal contact.
Long term systemic effects.
75 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Dermal contact.
Short term systemic effects.
89 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
98 mg of substance/m³

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
663 mg of substance/m³

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
246 mg of substance/m³

Final use:

Man exposed via the environment.

Exposure method:
Potential health effects:
DNEL :

Ingestion.
Long term systemic effects.
3.2 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Ingestion.
Short term systemic effects.
13.4 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Dermal contact.
Long term systemic effects.
38 mg/kg body weight/day

Exposure method:
Potential health effects:

Dermal contact.
Short term systemic effects.



SUSPENSION DIAMANTEE DE/SY - 09009/09016

DNEL : 44.5 mg/kg body weight/day

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 426 mg of substance/m3

Exposure method: Inhalation.
Potential health effects: Short term local effects.
DNEL : 123 mg of substance/m3

PROPYLENE GLYCOL (CAS: 57-55-6)

Final use:

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 168 mg of substance/m3

Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 10 mg of substance/m3

Final use:

Exposure method: Ingestion.
Potential health effects: Long term systemic effects.
DNEL : 85 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 213 mg/kg body weight/day

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 50 mg of substance/m3

Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 10 mg of substance/m3

ETHANOL (CAS: 64-17-5)

Final use:

Exposure method: Dermal contact.
Potential health effects: Long term local effects.
DNEL : 343 mg/kg body weight/day

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 950 mg of substance/m3

Exposure method: Inhalation.
Potential health effects: Short term local effects.
DNEL : 1900 mg of substance/m3



SUSPENSION DIAMANTEE DE/SY - 09009/09016

Final use:

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Man exposed via the environment.

Ingestion.
Long term systemic effects.
87 mg/kg body weight/day

Dermal contact.
Long term systemic effects.
206 mg/kg body weight/day

Inhalation.
Long term systemic effects.
114 mg of substance/m3

Inhalation.
Short term local effects.
950 mg of substance/m3

Predicted no effect concentration (PNEC):

PROPAN-2-OL (CAS: 67-63-0)

Environmental compartment:
PNEC : Fresh water.
140.9 mg/l

Environmental compartment:
PNEC : Sea water.
140.9 mg/l

Environmental compartment:
PNEC : Intermittent waste water.
140.9 mg/l

Environmental compartment:
PNEC : Waste water treatment plant.
2251 mg/l

BUTANONE (CAS: 78-93-3)

Environmental compartment:
PNEC : Soil.
22.5 mg/kg

Environmental compartment:
PNEC : Fresh water.
55.8 mg/l

Environmental compartment:
PNEC : Sea water.
55.8 mg/l

Environmental compartment:
PNEC : Intermittent waste water.
55.8 mg/l

Environmental compartment:
PNEC : Fresh water sediment.
284.74 mg/kg

Environmental compartment:
PNEC : Marine sediment.
284.74 mg/kg

Environmental compartment:
PNEC : Waste water treatment plant.
709 mg/l



SUSPENSION DIAMANTEE DE/SY - 09009/09016

2-BUTOXYETHANOL (CAS: 111-76-2)

Environmental compartment: PNEC :	Soil. 3.13 mg/kg
Environmental compartment: PNEC :	Fresh water. 8.8 mg/l
Environmental compartment: PNEC :	Sea water. 0.88 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 9.1 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 34.6 mg/kg
Environmental compartment: PNEC :	Marine sediment. 3.46 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 463 mg/l
Environmental compartment: PNEC :	Salt water predators (oral). 0.02

PROPYLENE GLYCOL (CAS: 57-55-6)

Environmental compartment: PNEC :	Soil. 50 mg/kg
Environmental compartment: PNEC :	Fresh water. 260 mg/l
Environmental compartment: PNEC :	Sea water. 26 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 183 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 572 mg/kg
Environmental compartment: PNEC :	Marine sediment. 57.2 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 20000 mg/l

ETHANOL (CAS: 64-17-5)

Environmental compartment: PNEC :	Soil. 0.63 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.96 mg/l



SUSPENSION DIAMANTEE DE/SY - 09009/09016

Environmental compartment: PNEC :	Sea water. 0.79 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 2.75 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 3.6 mg/kg
Environmental compartment: PNEC :	Marine sediment. 2.9 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 580 mg/l
Environmental compartment: PNEC :	Fresh water predators (oral). 0.72 mg/kg

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state : Fluid liquid.

Odour: Slight

Important health, safety and environmental information

pH (aqueous solution) : Neutre

pH : Not stated.

Slightly acidic.

Boiling point/boiling range : Not relevant.

Flash Point Interval : 23°C <= FP <= 55°C

Vapour pressure (50°C) : Not relevant.

Density : <1

Water solubility : Soluble.

Melting point/melting range : Not relevant.

Self-ignition temperature : Not relevant.

Decomposition point/decomposition range : Not relevant.



SUSPENSION DIAMANTEE DE/SY - 09009/09016

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

10.5. Incompatible materials

Keep away from :

- oxidising agents
- strong acids

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No data available.

11.1.1. Substances

Acute toxicity :

POLYETHYLENEGLYCOL (CAS: 25322-68-3)

Oral route : LD50 > 5.000 mg/kg
Species : Rat

POLYETHYLENEGLYCOL (PEG-6) (CAS: 25322-68-3)

Oral route : LD50 > 5.000 mg/kg
Species : Rat

POLYETHYLENEGLYCOL (CAS: 25322-68-3)

Oral route : LD50 > 5.000 mg/kg
Species : Rat

2-BUTOXYETHANOL (CAS: 111-76-2)

Oral route : LD50 = 1746 mg/kg
Species : Rat

Dermal route : LD50 > 2000 mg/kg
Species : Guinea pig



SUSPENSION DIAMANTEE DE/SY - 09009/09016

	OECD Guideline 402 (Acute Dermal Toxicity)
Inhalation route (n/a) :	LC50 = 2.21 mg/l Species : Rat
PROPYLENE GLYCOL (CAS: 57-55-6) Oral route :	LD50 > 22.000 mg/kg Species : Cat
Dermal route :	LD50 > 2.000 mg/kg Species : Rabbit
Inhalation route (n/a) :	LC50 > 317042 mg/m3 Species : Rabbit

Serious damage to eyes/eye irritation :

Irritating to eyes

11.1.2. Mixture

Respiratory or skin sensitisation :

Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

POLYETHYLENEGLYCOL (CAS: 25322-68-3)

Fish toxicity :	LC50 > 100 mg/l Species : Leuciscus idus
Crustacean toxicity :	EC50 > 100 mg/l Species : Daphnia magna Duration of exposure : 24 h

POLYETHYLENEGLYCOL (PEG-6) (CAS: 25322-68-3)

Fish toxicity :	LC50 > 100 mg/l Species : Leuciscus idus
Crustacean toxicity :	EC50 > 100 mg/l Species : Daphnia magna Duration of exposure : 24 h

POLYETHYLENEGLYCOL (CAS: 25322-68-3)

Fish toxicity :	LC50 > 100 mg/l Species : Leuciscus idus
Crustacean toxicity :	EC50 > 100 mg/l Species : Daphnia magna Duration of exposure : 24 h

PROPYLENE GLYCOL (CAS: 57-55-6)

Fish toxicity :	LC50 40.613 mg/l Species : Oncorhynchus mykiss
-----------------	---

SUSPENSION DIAMANTEE DE/SY - 09009/09016

	Duration of exposure : 96 h
Crustacean toxicity :	EC50 18.800 mg/l Species : Mysisidopsis bahia Duration of exposure : 72 h
	NOEC = 13.020 mg/l Species : Ceriodaphnia sp. Duration of exposure : 7 days
Algae toxicity :	ECr50 = 24.200 mg/l Species : Selenastrum capricornutum Duration of exposure : 72 h OECD Guideline 201 (Alga, Growth Inhibition Test)
2-BUTOXYETHANOL (CAS: 111-76-2)	
Fish toxicity :	LC50 = 1474 mg/l Species : Oncorhynchus mykiss Duration of exposure : 96 h OECD Guideline 203 (Fish, Acute Toxicity Test)
Crustacean toxicity :	EC50 = 1550 mg/l Species : Daphnia magna Duration of exposure : 48 h OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

BUTANONE (CAS: 78-93-3)	
Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.
2-BUTOXYETHANOL (CAS: 111-76-2)	
Biodegradability :	Rapidly degradable.
PROPYLENE GLYCOL (CAS: 57-55-6)	
Biodegradability :	Rapidly degradable.
POLYETHYLENEGLYCOL (CAS: 25322-68-3)	
Chemical oxygen demand :	DCO = 1660 mg/kg
Five-day biochemical oxygen demand :	DBO5 < 10000 mg/kg
Biodegradability :	Rapidly degradable.
POLYETHYLENEGLYCOL (PEG-6) (CAS: 25322-68-3)	
Chemical oxygen demand :	DCO = 1660 mg/kg
Five-day biochemical oxygen demand :	DBO5 < 10000 mg/kg



SUSPENSION DIAMANTEE DE/SY - 09009/09016

Biodegradability : Rapidly degradable.

POLYETHYLENEGLYCOL (CAS: 25322-68-3)

Chemical oxygen demand : DCO = 1660 mg/kg

Five-day biochemical oxygen demand : DBO5 < 10000 mg/kg

Biodegradability : Rapidly degradable.

12.3. Bioaccumulative potential

12.3.1. Substances

2-BUTOXYETHANOL (CAS: 111-76-2)

Octanol/water partition coefficient : log K_{ow} = 0.76

PROPYLENE GLYCOL (CAS: 57-55-6)

Octanol/water partition coefficient : log K_{ow} = -1.07

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 1 : Slightly hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Respect the local and national regulations

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Respect the local and national regulations

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2019).

14.1. UN number

1993

14.2. UN proper shipping name

UN1993=FLAMMABLE LIQUID, N.O.S.

(ethanol)

SUSPENSION DIAMANTEE DE/SY - 09009/09016

14.3. Transport hazard class(es)

- Classification :



3

14.4. Packing group

III

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	30	5 L	274 601	E1	3	D/E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	3	-	III	5 L	F-E, S-E	223 274 955	E1	Category A	-

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	3	III	355	60 L	366	220 L	A3	E1
	3	3	III	Y344	10 L	-	-	A3	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2019/521 (ATP 12)

- Container information:

No data available.

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 1 : Slightly hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.



SUSPENSION DIAMANTEE DE/SY - 09009/09016

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations :

DNEL : Derived No-Effect Level
PNEC : Predicted No-Effect Concentration
ADR : European agreement concerning the international carriage of dangerous goods by Road.
IMDG : International Maritime Dangerous Goods.
IATA : International Air Transport Association.
ICAO : International Civil Aviation Organisation
RID : Regulations concerning the International carriage of Dangerous goods by rail.
WGK : Wassergefährdungsklasse (Water Hazard Class).
GHS02 : Flame
PBT: Persistent, bioaccumulable and toxic.
vPvB : Very persistent, very bioaccumulable.
SVHC : Substances of very high concern.