



OXYDE D'ALUMINE - 12008 A 12018

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : OXYDE D'ALUMINE

Product code : 12008 A 12018.

UFI : RP00-V0S0-300S-F4UE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Abrasive for polishing or lapping

1.3. Details of the supplier of the safety data sheet

Registered company name : PRESI S.A.S.

Address : 11 Rue du vercors.38320.EYBENS.France.

Telephone : +33 (0)4.76.72.00.21. Fax : +33 (0)4.76.72.05.84.

presi@presi.com

www.presi.com

1.4. Emergency telephone number : +33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

This substance does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This substance does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

This substance does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :

2.3. Other hazards

In use, may form flammable/explosive dust-air mixture.

The substance does not fulfil the PBT or vPvP criteria in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 1344-28-1 EC: 215-691-6 REACH: 01-2119529248-35-0009 ALUMINIUM OXIDE		[1]	100%

Specific concentration limits:

Identification	Specific concentration limits	ATE
CAS: 1344-28-1 EC: 215-691-6 REACH: 01-2119529248-35-0009 ALUMINIUM OXIDE		inhalation: ATE = 2.3 mg/l (dust/mist) oral: ATE = 10000 mg/kg BW



OXYDE D'ALUMINE - 12008 A 12018

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

Move to fresh air

If symptoms persist, call a physician

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

Rinse immediately with plenty of water, also under the eyelids

Consult a physician if necessary

In the event of splashes or contact with skin :

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

Wash off immediately with soap and plenty of water

In the event of swallowing :

Seek medical attention, showing the label.

Do not induce vomiting without medical advice

Clean mouth with water and drink afterwards plenty of water

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

Water, foam, sand, powder or CO₂, according to the surrounding materials

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Retrieve the product by mechanical means (sweeping/vacuuming) : do not generate dust.



OXYDE D'ALUMINE - 12008 A 12018

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the substance is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Safe handling advice

Avoid contact with skin and eyes

Technical measures / Precautions

Provide sufficient air exchange and/or ventilation in work rooms

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the substance is used.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and animals feeding stuffs

Do not smoke

Keep the container tightly closed and away from dampness

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1344-28-1	10 mg/m3	-	-	-	-

- Canada / Ontario (Control of exposure to biological or chemical agents, regulation 491/2009) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1344-28-1	10 mg/m3	-	-	-	T

- Canada / Quebec (Regulations on occupational health and safety) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1344-28-1	10 mg/m3			Pt. note 1	

- France (INRS - ED984 / 2020-1546) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
1344-28-1	-	10	-	-	-	-

- Japan (JSOH, 17/05/2018) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1344-28-1	0.5 mg/m3	-	-	-	R

- Switzerland (SUVAPRO 2019) :

CAS	VME	VLE	Valeur plafond	Notations
1344-28-1	3 ppm	24 mg/m ³		

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1344-28-1	4 mg/m ³				

OXYDE D'ALUMINE - 12008 A 12018

8.2. Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Before handling powders or dust emission, wear mask goggles in accordance with standard EN166.

Protective glasses completely dust-tight

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

To place at the disposal of the users suitable gloves

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

To envisage normal working clothes

- Respiratory protection

Avoid inhaling dust.

Type of FFP mask :

Wear a disposable half-mask dust filter in accordance with standard EN149/A1.

Mask of protection suited for the dust

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state : Powder or dust.

Colour

Unspecified

Odour

Odour threshold : Not stated.

Melting point

Melting point/melting range : 2050 °C.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not specified.

Flammability

Flammability (solid, gas) : Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) : Not stated.

Explosive properties, upper explosivity limit (%) : Not stated.



OXYDE D'ALUMINE - 12008 A 12018

Flash point

Flash point interval : Not relevant.

Auto-ignition temperature

Self-ignition temperature : Not specified.

Decomposition temperature

Decomposition point/decomposition range : Not specified.

pH

pH : Not relevant.

pH (aqueous solution) : Not stated.

Kinematic viscosity

Viscosity : Not stated.

Solubility

Water solubility : Soluble.

Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Not relevant.

Density and/or relative density

Density : 0.8-1.3 g/cm³

Relative vapour density

Vapour density : Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This substance is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- formation of dusts

Dusts can form an explosive mixture with air.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

No data available.



OXYDE D'ALUMINE - 12008 A 12018

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No data available.

11.1.1. Substances

Acute toxicity :

ALUMINIUM OXIDE (CAS: 1344-28-1)

Oral route : LD50 = 10000 mg/kg
Species : Rat

Inhalation route (Dusts/mist) : LC50 = 2.3 mg/l
Species : Rat

11.2. Information on other hazards

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

ALUMINIUM OXIDE (CAS: 1344-28-1)

Fish toxicity : LC50 > 100 mg/l
Species : Salmo trutta
OECD Guideline 203 (Fish, Acute Toxicity Test)

NOEC > 100 mg/l
Duration of exposure : 96 h

Crustacean toxicity : EC50 > 100 mg/l
Species : Daphnia magna
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

NOEC > 100 mg/l
Species : Daphnia magna
Duration of exposure : 48 h

Algae toxicity : ECr50 > 100 mg/l
Species : Selenastrum capricornutum

12.2. Persistence and degradability

12.2.1. Substances

ALUMINIUM OXIDE (CAS: 1344-28-1)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.



OXYDE D'ALUMINE - 12008 A 12018

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

Nicht wassergefährdend : Not hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the substance and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number or ID number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

- Container information:

No data available.

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

Nicht wassergefährdend : Not hazardous for water.



OXYDE D'ALUMINE - 12008 A 12018

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the substance and not as a guarantee of the properties thereof.

Abbreviations :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

NOEC : The concentration with no observed effect.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

BW : Body Weight

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.