



JET PUR - 19007

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : JET PUR

Product code : 19007.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaning for sample

1.3. Details of the supplier of the safety data sheet

Registered company name : PRESI S.A.S.

Address : 11 Rue du vercors.38320.EYBENS.France.

Telephone : +33 (0)4.76.72.00.21. Fax : +33 (0)4.76.72.05.84.

presi@presi.com

www.presi.com

1.4. Emergency telephone number : +33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02

Signal Word :

DANGER

Hazard statements :

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

Precautionary statements - Prevention :

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211

Do not spray on an open flame or other ignition source.

P251

Do not pierce or burn, even after use.

P261

Avoid breathing dust/fume/gas/mist/vapours/spray.

P271

Use only outdoors or in a well-ventilated area.

Precautionary statements - Storage :

P410 + P412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

JET PUR - 19007

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32 BUTANE	GHS02 Dgr Flam. Gas 1, H220	C [1] [7]	50 \leq x % < 100
INDEX: 601-004-00-0 CAS: 75-28-5 EC: 200-857-2 AND ISOBUTANE	GHS02, GHS04 Dgr Flam. Gas 1, H220	C [1] [7]	10 \leq x % < 25
CAS: 74-98-6 EC: 200-827-9 REACH: 01-2119486944-21 PROPANE	GHS02 Dgr Flam. Gas 1, H220	[1] [7]	10 \leq x % < 25
CAS: 124-38-9 EC: 204-696-9 CO2 DIOXYDE DE CARBONE / CARBON DIOXIDE		[1] [7]	2.5 \leq x % < 10

(Full text of H-phrases: see section 16)

Information on ingredients :

[7] Propellant gas

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

Move to fresh air

If symptoms persist, call a physician

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Consult a physician if necessary

In the event of splashes or contact with skin :

Take off all contaminated clothing immediately

Wash off immediately with soap and plenty of water

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.



JET PUR - 19007

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

In the event of fire, wear self-contained breathing apparatus

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.



JET PUR - 19007

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Keep the container tightly closed in a cool, well ventilated place

Keep the container away from dampness

Do not smoke

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

Do not unpack

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m ³ :	VME-ppm :	VLE-mg/m ³ :	VLE-ppm :	Notes :
124-38-9	9000	5000	-	-	-

JET PUR - 19007

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	1000 ppm				
75-28-5	1000 ppm				
74-98-6	1000 ppm				
124-38-9	5000 ppm	30.000 ppm			

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME :	VME :	Excess	Notes
106-97-8		1000 ppm 2400 mg/m ³		4(II)
75-28-5		1000 ppm 2400 mg/m ³		4(II)
74-98-6		1000 ppm 1800 mg/m ³		4(II)
124-38-9		5000 ppm 9100 mg/m ³		2(II)

- Canada / Ontario (Control of exposure to biological or chemical agents, regulation 491/2009) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	800 ppm				
75-28-5	800 ppm				
74-98-6	1.000 ppm				

- Canada / Quebec (Regulations on occupational health and safety) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	800 ppm 1900 mg/m ³				
74-98-6	1000 ppm 1800 mg/m ³				
124-38-9	5000 ppm 9000 mg/m ³	30000 ppm 54000 mg/m ³			

- France (INRS - ED984 / 2019-1487) :

CAS	VME-ppm :	VME-mg/m ³ :	VLE-ppm :	VLE-mg/m ³ :	Notes :	TMP No :
106-97-8	800	1900	-	-	-	-
124-38-9	5000	9000	-	-	-	-

- Japan (JSOH, 17/05/2018) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	500 ppm 1200 mg/m ³				
75-28-5	500 ppm	-	-	-	-
124-38-9	5000 ppm 9000 mg/m ³				

- Switzerland (SUVAPRO 2017) :

CAS	VME	VLE	Valeur plafond	Notations
106-97-8	800 ppm 1900 mg/m ³	3200 ppm 7200 mg/m ³		
75-28-5	800 ppm 1900 mg/m ³	3200 ppm 7200 mg/m ³		
74-98-6	1000 ppm 1800 mg/m ³	4000 ppm 7200 mg/m ³		
124-38-9	5000 ppm 9000 mg/m ³			

- USA / NIOSH IDLH (National Institute for Occupational Safety and Health, Immediately Dangerous to Life or Health Concentrations) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	800 ppm 1900 mg/m ³				

JET PUR - 19007

75-28-5	800 ppm 1900 mg/m ³				
74-98-6	1000 ppm 1800 mg/m ³				
124-38-9	5000 ppm 9000 mg/m ³	30 ppm 54 mg/m ³			

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm 1450 mg/m ³	750 ppm 1810 mg/m ³		Carc	
124-38-9	5000 ppm 9150 mg/m ³	15000 ppm 27400 mg/m ³			

8.2. Exposure controls

Appropriate engineering controls

- Avoid contact with skin, eyes and clothing
- Not to breathe pulverization

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVA (Polyvinyl alcohol)

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category :

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- AX (Brown)

Particle filter according to standard EN143 :

- P1 (White)



JET PUR - 19007

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state : Fluid liquid.
Spray.

Important health, safety and environmental information

pH : Not relevant.
Boiling point/boiling range : Not specified.
Flash point interval : Not relevant.
Vapour pressure (50°C) : Not relevant.
Density : < 1
Water solubility : Insoluble.
Melting point/melting range : Not specified.
Self-ignition temperature : Not specified.
Decomposition point/decomposition range : Not specified.
Chemical combustion heat : ≥ 30 kJ/g.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat

10.5. Incompatible materials

Keep away from :

- oxidising agents

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
 - carbon dioxide (CO₂)
-

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances

Acute toxicity :

PROPANE (CAS: 74-98-6)



JET PUR - 19007

Inhalation route (n/a) : LC50 = 658 ppm

BUTANE (CAS: 106-97-8)

Inhalation route (n/a) : LC50 658
Species : Rat

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

PROPANE (CAS: 74-98-6)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

12.3.1. Substances

PROPANE (CAS: 74-98-6)

Octanol/water partition coefficient : log K_{ow} = 2.3

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

Nicht wassergefährdend : Not hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Respect the local and national regulations

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Respect the local and national regulations

JET PUR - 19007

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2020).

14.1. UN number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification :



2.1

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	2	See SP63	-	See SP277	F-D, S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A802	E0
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 75/324/CEE modified by directive 2013/10/UE

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/217 (ATP 14)

- Container information:

No data available.

- Particular provisions :

No data available.

