



LUBRIFIANT GH - 10009/10022

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : LUBRIFIANT GH

Product code : 10009/10022.

LUBRICANT GH / SCHMIERMITTEL GH / LUBRIFIANT GH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricant for polishing

1.3. Details of the supplier of the safety data sheet

Registered company name : PRESI S.A.

Address : 11 Rue du vercors.38320.EYBENS.France.

Telephone : +33 (0)4.76.72.00.21. Fax : +33 (0)4.76.72.05.84.

presi@presi.com

www.presi.com

1.4. Emergency telephone number : +33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

No labelling requirements for this mixture.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 57-55-6 EC: 200-338-0 REACH: 01-2119456809-23 PROPYLENE GLYCOL		[1]	25 \leq x % < 50

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.



LUBRIFIANT GH - 10009/10022

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

Move to fresh air

If symptoms persist, call a physician

In the event of splashes or contact with eyes :

Rinse immediately with plenty of water, also under the eyelids

In the event of splashes or contact with skin :

Wash off immediately with soap and plenty of water

In the event of swallowing :

Seek medical attention, showing the label.

Clean mouth with water and drink afterwards plenty of water

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist

- foam

- carbon dioxide (CO₂)

- powder

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO₂)

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.



LUBRIFIANT GH - 10009/10022

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Technical measures / Precautions

Provide sufficient air exchange and/or ventilation in work rooms

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Keep the container tightly closed in a cool, well ventilated place

Keep away from heat

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- Canada / Ontario (Control of exposure to biological or chemical agents, regulation 491/2009) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
57-55-6	50 (V) ppm 155 mg/m ³				

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
57-55-6	150 ppm 474 mg/m ³	- ppm - mg/m ³			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

PROPYLENE GLYCOL (CAS: 57-55-6)

Final use:

Exposure method:

Potential health effects:

DNEL :

Exposure method:

Potential health effects:

DNEL :

Workers.

Inhalation.

Long term systemic effects.

168 mg of substance/m³

Inhalation.

Long term local effects.

10 mg of substance/m³

LUBRIFIANT GH - 10009/10022

Final use:

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Consumers.

Ingestion.
Long term systemic effects.
85 mg/kg body weight/day

Dermal contact.
Long term systemic effects.
213 mg/kg body weight/day

Inhalation.
Long term systemic effects.
50 mg of substance/m³

Inhalation.
Long term local effects.
10 mg of substance/m³

Predicted no effect concentration (PNEC):

PROPYLENE GLYCOL (CAS: 57-55-6)

Environmental compartment:
PNEC : Soil.
50 mg/kg

Environmental compartment:
PNEC : Fresh water.
260 mg/l

Environmental compartment:
PNEC : Sea water.
26 mg/l

Environmental compartment:
PNEC : Intermittent waste water.
183 mg/l

Environmental compartment:
PNEC : Fresh water sediment.
572 mg/kg

Environmental compartment:
PNEC : Marine sediment.
57.2 mg/kg

Environmental compartment:
PNEC : Waste water treatment plant.
20000 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

Safety glasses



LUBRIFIANT GH - 10009/10022

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Breathing apparatus needed only when aerosol or mist is formed

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state : Fluid liquid.

Important health, safety and environmental information

pH : 4.00 - 7.
Slightly acidic.

Boiling point/boiling range : 184°C

Flash Point : 104.00 °C.

Vapour pressure (50°C) : Not relevant.

Density : 1.03 g/cm³ (20°C)

Water solubility : Soluble.

Partition coefficient: n-octanol/water : -1.07

Melting point/melting range : -59 °C.

Self-ignition temperature : Not specified.

Decomposition point/decomposition range : Not specified.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- frost
- heat

10.5. Incompatible materials

Keep away from :

- strong oxidising agents

Zinc

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)



LUBRIFIANT GH - 10009/10022

- carbon dioxide (CO₂)

Incomplete combustion produces toxic gases, such as CO, CO₂, various forms of hydrocarbons, aldehydes, etc..., and soots

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No data available.

11.1.1. Substances

Acute toxicity :

PROPYLENE GLYCOL (CAS: 57-55-6)

Oral route : LD50 > 22.000 mg/kg
Species : Cat

Dermal route : LD50 > 2.000 mg/kg
Species : Rabbit

Inhalation route (Dusts/mist) : LC50 > 317042 mg/m³
Species : Rabbit

11.1.2. Mixture

Respiratory or skin sensitisation :

Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

PROPYLENE GLYCOL (CAS: 57-55-6)

Fish toxicity : LC50 40.613 mg/l
Species : *Oncorhynchus mykiss*
Duration of exposure : 96 h

Crustacean toxicity : EC50 18.800 mg/l
Species : *Mysidopsis bahia*
Duration of exposure : 72 h

NOEC = 13.020 mg/l
Species : *Ceriodaphnia* sp.
Duration of exposure : 7 days

Algae toxicity : ECr50 = 24.200 mg/l
Species : *Selenastrum capricornutum*
Duration of exposure : 72 h
OECD Guideline 201 (Alga, Growth Inhibition Test)

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

PROPYLENE GLYCOL (CAS: 57-55-6)

Biodegradability : Rapidly degradable.



LUBRIFIANT GH - 10009/10022

12.3. Bioaccumulative potential

12.3.1. Substances

PROPYLENE GLYCOL (CAS: 57-55-6)

Octanol/water partition coefficient : log K_{ow} = -1.07

12.4. Mobility in soil

Do not discharge into surface water or sanitary sewer system

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 1 : Slightly hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Respect the local and national regulations

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Respect the local and national regulations

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-



LUBRIFIANT GH - 10009/10022

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)

- Container information:

No data available.

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 1 : Slightly hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.