



**SUSPENSION DIAMANTEE LD33 - 20200 A 20205**

## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : SUSPENSION DIAMANTEE LD33  
Product code : 20200 A 20205.  
20210-20215; 20191-20195; 20503-20505

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Diamonds suspension for polishing or grinding

#### 1.3. Details of the supplier of the safety data sheet

Registered company name : PRESI S.A.S.  
Address : 11 Rue du vercors.38320.EYBENS.France.  
Telephone : +33 (0)4.76.72.00.21. Fax : +33 (0)4.76.72.05.84.  
presi@presi.com  
www.presi.com

#### 1.4. Emergency telephone number : +33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

### SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### In compliance with EC regulation No. 1272/2008 and its amendments.

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

#### 2.2. Label elements

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :  
EUH210 Safety data sheet available on request.  
Hazard statements :

#### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

### SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

##### Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 64-17-5 EC: 200-578-6 REACH: 01-2119457610-43-0000 ETHANOL	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319	[1]	2.5 $\leq$ x % < 10
CAS: 78-93-3 EC: 201-159-0 REACH: 01-2119457290-43-XXXX BUTANONE	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]	0 $\leq$ x % < 1



**SUSPENSION DIAMANTEE LD33 - 20200 A 20205**

CAS: 67-63-0 EC: 200-661-7 REACH: 01-2119457558-25-XXXX PROPAN-2-OL	GHS07 Wng Eye Irrit. 2, H319 STOT SE 3, H336	[1]	0 <= x % < 1
CAS: 14808-60-7 EC: 238-878-4 QUARTZ		[1]	0 <= x % < 1

(Full text of H-phrases: see section 16)

**Information on ingredients :**

[1] Substance for which maximum workplace exposure limits are available.

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.  
NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures**

**In the event of exposure by inhalation :**

Move to fresh air  
If symptoms persist, call a physician

**In the event of splashes or contact with eyes :**

Rinse immediately with plenty of water, also under the eyelids

**In the event of splashes or contact with skin :**

Take off all contaminated clothing immediately  
Wash off immediately with soap and plenty of water

**In the event of swallowing :**

Seek medical attention, showing the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

**SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

**5.1. Extinguishing media**

**Suitable methods of extinction**

In the event of a fire, use :  
- sprayed water or water mist  
- foam  
- multipurpose ABC powder  
- BC powder  
- carbon dioxide (CO<sub>2</sub>)

**Unsuitable methods of extinction**

In the event of a fire, do not use :  
- water jet

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)



**SUSPENSION DIAMANTEE LD33 - 20200 A 20205**

- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

No data available.

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

**Fire prevention :**

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**Occupational exposure limits :**

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m <sup>3</sup> :	VME-ppm :	VLE-mg/m <sup>3</sup> :	VLE-ppm :	Notes :
78-93-3	600	200	900	300	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5		1000 ppm		A3	
78-93-3	200 ppm	300 ppm		BEI	
67-63-0	200 ppm	400 ppm		A4; BEI	

**SUSPENSION DIAMANTEE LD33 - 20200 A 20205**

14808-60-7	0.05 mg/m <sup>3</sup>	-	-	-	R
------------	------------------------	---	---	---	---

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME :	VME :	Excess	Notes
64-17-5		200 ppm 380 mg/m <sup>3</sup>		4(II)
78-93-3		200 ppm 600 mg/m <sup>3</sup>		1(I)
67-63-0		200 ppm 500 mg/m <sup>3</sup>		2(II)

- Canada / Ontario (Control of exposure to biological or chemical agents, regulation 491/2009) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
67-63-0	200 ppm	400 ppm	-	-	-
14808-60-7	0.10 (R) mg/m <sup>3</sup>				

- Canada / Quebec (Regulations on occupational health and safety) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm 1880 mg/m <sup>3</sup>				
78-93-3	50 ppm 150 mg/m <sup>3</sup>	100 ppm 300 mg/m <sup>3</sup>			
67-63-0	400 ppm 983 mg/m <sup>3</sup>	500 ppm 1230 mg/m <sup>3</sup>			
14808-60-7	0.1 mg/m <sup>3</sup>			Pr.C2.EM	

- France (INRS - ED984 / 2019-1487) :

CAS	VME-ppm :	VME-mg/m <sup>3</sup> :	VLE-ppm :	VLE-mg/m <sup>3</sup> :	Notes :	TMP No :
64-17-5	1000	1900	5000	9500	-	84
78-93-3	200	600	300	900	*	84
67-63-0	-	-	400	980	-	84
14808-60-7	-	0.1 A	-	-	-	25

- Japan (JSOH, 17/05/2018) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
78-93-3	200 ppm 590 mg/m <sup>3</sup>				
67-63-0			400 ppm 980 mg/m <sup>3</sup>		

- Switzerland (SUVAPRO 2017) :

CAS	VME	VLE	Valeur plafond	Notations
64-17-5	500 ppm 960 mg/m <sup>3</sup>	1000 ppm 1920 mg/m <sup>3</sup>		SSC
78-93-3	200 ppm 590 mg/m <sup>3</sup>	200 ppm 590 mg/m <sup>3</sup>		R B SSC
67-63-0	200 ppm 500 mg/m <sup>3</sup>	400 ppm 1000 mg/m <sup>3</sup>		B SSC
14808-60-7	0.15 a mg/m <sup>3</sup>			P C1 SSC

- USA / NIOSH IDLH (National Institute for Occupational Safety and Health, Immediately Dangerous to Life or Health Concentrations) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	-	-	3300	-	-
78-93-3	200 ppm 590 mg/m <sup>3</sup>	300 ppm 885 mg/m <sup>3</sup>			
67-63-0	400 ppm 980 mg/m <sup>3</sup>	500 ppm 1225 mg/m <sup>3</sup>			
14808-60-7	-	-	50	-	-

**SUSPENSION DIAMANTEE LD33 - 20200 A 20205**

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm 1920 mg/m <sup>3</sup>	- ppm - mg/m <sup>3</sup>			
78-93-3	200 ppm 600 mg/m <sup>3</sup>	300 ppm 899 mg/m <sup>3</sup>		Sk. BMGV	
67-63-0	400 ppm 999 mg/m <sup>3</sup>	500 ppm 1250 mg/m <sup>3</sup>			
14808-60-7	0.3 mg/m <sup>3</sup>	-	-	-	R

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

PROPAN-2-OL (CAS: 67-63-0)

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Dermal contact.  
Long term systemic effects.  
888 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
500 mg of substance/m<sup>3</sup>

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Consumers.**

Ingestion.  
Long term systemic effects.  
26 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Dermal contact.  
Long term systemic effects.  
319 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
89 mg of substance/m<sup>3</sup>

BUTANONE (CAS: 78-93-3)

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Dermal contact.  
Long term systemic effects.  
1161 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
600 mg of substance/m<sup>3</sup>

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Consumers.**

Ingestion.  
Long term systemic effects.  
31 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Dermal contact.  
Long term systemic effects.  
412 mg/kg body weight/day

Exposure method:

Inhalation.



**SUSPENSION DIAMANTEE LD33 - 20200 A 20205**

Potential health effects:  
DNEL : Long term systemic effects.  
106 mg of substance/m3

**ETHANOL (CAS: 64-17-5)**

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Dermal contact.  
Long term local effects.  
343 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
950 mg of substance/m3

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Short term local effects.  
1900 mg of substance/m3

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Man exposed via the environment.**

Ingestion.  
Long term systemic effects.  
87 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Dermal contact.  
Long term systemic effects.  
206 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
114 mg of substance/m3

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Short term local effects.  
950 mg of substance/m3

**Predicted no effect concentration (PNEC):**

**PROPAN-2-OL (CAS: 67-63-0)**

Environmental compartment:  
PNEC :

Soil.  
28 mg/kg

Environmental compartment:  
PNEC :

Fresh water.  
140.9 mg/l

Environmental compartment:  
PNEC :

Sea water.  
140.9 mg/l

Environmental compartment:  
PNEC :

Intermittent waste water.  
140.9 mg/l

Environmental compartment:  
PNEC :

Waste water treatment plant.  
2251 mg/l

**BUTANONE (CAS: 78-93-3)**

Environmental compartment:

Soil.

**SUSPENSION DIAMANTEE LD33 - 20200 A 20205**

PNEC :	22.5 mg/kg
Environmental compartment: PNEC :	Fresh water. 55.8 mg/l
Environmental compartment: PNEC :	Sea water. 55.8 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 55.8 mg/l
ETHANOL (CAS: 64-17-5)	
Environmental compartment: PNEC :	Soil. 0.63 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.96 mg/l
Environmental compartment: PNEC :	Sea water. 0.79 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 2.75 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 3.6 mg/kg
Environmental compartment: PNEC :	Marine sediment. 2.9 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 580 mg/l
Environmental compartment: PNEC :	Fresh water predators (oral). 0.72 mg/kg

## 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.



**SUSPENSION DIAMANTEE LD33 - 20200 A 20205**

**- Hand protection**

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties :

- Impervious gloves in accordance with standard EN ISO 374-2

**- Body protection**

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**General information :**

Physical state : Fluid liquid.

**Important health, safety and environmental information**

pH : Not stated.  
Slightly acidic.

Boiling point/boiling range : Not relevant.

Flash Point Interval : 60°C < FP <= 93°C

Vapour pressure (50°C) : Not relevant.

Density : > 1

Water solubility : Soluble.

Melting point/melting range : Not relevant.

Self-ignition temperature : Not specified.

Decomposition point/decomposition range : Not relevant.

**9.2. Other information**

No data available.

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

No data available.

**10.5. Incompatible materials**

No data available.

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)



**SUSPENSION DIAMANTEE LD33 - 20200 A 20205**

---

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

No data available.

**11.1.1. Substances**

**Acute toxicity :**

PROPAN-2-OL (CAS: 67-63-0)

Oral route :

LD50 = 5840 mg/kg  
Species : Rat  
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route :

LD50 = 13900 mg/kg  
Species : Rabbit  
OECD Guideline 402 (Acute Dermal Toxicity)  
  
Species : Rat

BUTANONE (CAS: 78-93-3)

Oral route :

LD50 > 2193 mg/kg  
Species : Rat  
OECD Guideline 423 (Acute Oral toxicityAcute Toxic Class Method)

Dermal route :

LD50 > 5000 mg/kg  
Species : Rabbit  
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (n/a) :

LC50 = 34 mg/l  
Species : Rat

ETHANOL (CAS: 64-17-5)

Oral route :

LD50 = 10470 mg/kg  
Species : Cat  
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route :

LD50 > 2000 mg/kg  
Species : Rabbit  
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (n/a) :

LC50 = 51 mg/l  
Species : Rabbit  
OECD Guideline 403 (Acute Inhalation Toxicity)

**11.1.2. Mixture**

No toxicological data available for the mixture.

---

**SECTION 12 : ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.1.1. Substances**

PROPAN-2-OL (CAS: 67-63-0)

Fish toxicity :

LC50 = 9640 mg/l  
Species : Pimephales promelas



**SUSPENSION DIAMANTEE LD33 - 20200 A 20205**

	Duration of exposure : 96 h OECD Guideline 203 (Fish, Acute Toxicity Test)
Algae toxicity :	ECr50 = 100 mg/l Species : Scenedesmus subspicatus Duration of exposure : 72 h
BUTANONE (CAS: 78-93-3) Fish toxicity :	LC50 = 2993 mg/l Species : Pimephales promelas Duration of exposure : 96 h OECD Guideline 203 (Fish, Acute Toxicity Test)
Crustacean toxicity :	EC50 = 308 mg/l Species : Daphnia magna Duration of exposure : 48 h OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Algae toxicity :	ECr50 = 1972 mg/l Species : Pseudokirchnerella subcapitata Duration of exposure : 72 h
ETHANOL (CAS: 64-17-5) Fish toxicity :	LC50 = 13000 mg/l Species : Oncorhynchus mykiss Duration of exposure : 96 h OECD Guideline 203 (Fish, Acute Toxicity Test)
Crustacean toxicity :	EC50 = 858 mg/l Species : Artemia salina Duration of exposure : 48 h OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Algae toxicity :	ECr50 = 275 mg/l Species : Chlorella vulgaris Duration of exposure : 72 h

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability**

**12.2.1. Substances**

PROPAN-2-OL (CAS: 67-63-0)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

BUTANONE (CAS: 78-93-3)

Biodegradability :

Rapidly degradable.

ETHANOL (CAS: 64-17-5)

Biodegradability :

Rapidly degradable.



**SUSPENSION DIAMANTEE LD33 - 20200 A 20205**

---

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

No data available.

**German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 1 : Slightly hazardous for water.

---

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

---

**SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

**14.1. UN number**

-

**14.2. UN proper shipping name**

-

**14.3. Transport hazard class(es)**

-

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

-

---

**SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/217 (ATP 14)

**- Container information:**

No data available.

**- Particular provisions :**

No data available.

---



**SUSPENSION DIAMANTEE LD33 - 20200 A 20205**

---

**- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 1 : Slightly hazardous for water.

**15.2. Chemical safety assessment**

No data available.

---

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

**Abbreviations :**

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.