



## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : LIQUIDE DIAMANTE REF 3 HOUG 10 ET 6 HOUG 10  
Product code : 33083-33084.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Diamonds suspension for polishing or grinding

#### 1.3. Details of the supplier of the safety data sheet

Registered company name : PRESI S.A.S.  
Address : 11 Rue du vercors.38320.EYBENS.France.  
Telephone : +33 (0)4.76.72.00.21. Fax : +33 (0)4.76.72.05.84.  
presi@presi.com  
www.presi.com

#### 1.4. Emergency telephone number : +33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

### SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Repeated exposure may cause skin dryness or cracking (EUH066).

Aspiration hazard, Category 1 (Asp. Tox. 1, H304).

This substance does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This substance does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

#### 2.2. Label elements

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS08

Signal Word :

DANGER

Product identifiers :

EC 920-360-3      LOW VISCOSITY MINERAL OIL

Hazard statements :

H304      May be fatal if swallowed and enters airways.

EUH066      Repeated exposure may cause skin dryness or cracking.

Precautionary statements - Response :

P301 + P310      IF SWALLOWED: Immediately call a POISON CENTER/doctor/...

P331      Do NOT induce vomiting.

Precautionary statements - Storage :

P405      Store locked up.

Precautionary statements - Disposal :

P501      Dispose of contents/container to ...

**LIQUIDE DIAMANTE REF 3 HOUG 10 ET 6 HOUG 10 - 33083-33084**

**2.3. Other hazards**

The substance does not fulfil the PBT or vPvP criteria in accordance with annexe XIII of the REACH regulations EC 1907/2006.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1. Substances**

**Composition :**

Identification	(EC) 1272/2008	Note	%
EC: 920-360-3 REACH: 01-2119448343-11 LOW VISCOSITY MINERAL OIL	GHS08 Dgr Asp. Tox. 1, H304		100%

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures**

**In the event of exposure by inhalation :**

Move to fresh air

If symptoms persist, call a physician

**In the event of splashes or contact with eyes :**

Rinse immediately with plenty of water, also under the eyelids

Consult a physician if necessary

**In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**In the event of swallowing :**

Do not give the patient anything orally.

Seek medical attention, showing the label.

If swallowed accidentally, do not allow to drink, do not induce vomiting and transfer to hospital immediately by ambulance. Show the label to the doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

**SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

**5.1. Extinguishing media**

**Suitable methods of extinction**

In the event of a fire, use :

- powder

- carbon dioxide (CO<sub>2</sub>)

- sprayed water or water mist

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet



---

**LIQUIDE DIAMANTE REF 3 HOUG 10 ET 6 HOUG 10 - 33083-33084**

---

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

In the event of fire, wear self-contained breathing apparatus

---

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Avoid any contact with the skin and eyes.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

---

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the substance is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

**Fire prevention :**

Never inhale this substance.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the substance is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep away from food and drink, including those for animals.

Keep in a cool dry place

Keep the container tightly closed and protected from moisture

**Packaging**

Always keep in packaging made of an identical material to the original.

**LIQUIDE DIAMANTE REF 3 HOUG 10 ET 6 HOUG 10 - 33083-33084**

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

No data available.

**8.2. Exposure controls**

**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

**- Hand protection**

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- Neoprene® (Polychloroprene)

Recommended properties :

- Impervious gloves in accordance with standard EN ISO 374-2

**- Body protection**

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**General information :**

Physical state : Fluid liquid.

**Important health, safety and environmental information**

pH : Not relevant.

Boiling point/boiling range : 255°C



**LIQUIDE DIAMANTE REF 3 HOUG 10 ET 6 HOUG 10 - 33083-33084**

Flash Point :	122.00 °C.
Explosive properties, lower explosivity limit (%) :	0.45
Explosive properties, upper explosivity limit (%) :	5,0
Vapour pressure (50°C) :	Not relevant.
Density :	0,82 g/cm <sup>3</sup> (15 °C)
Water solubility :	Insoluble.
Viscosity :	3 mm <sup>2</sup> /s (40 °C)
Viscosity:	v < 7 mm <sup>2</sup> /s (40°C)
Melting point/melting range :	Not relevant.
Self-ignition temperature :	Not relevant.
Decomposition point/decomposition range :	Not relevant.

**9.2. Other information**

No data available.

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This substance is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Avoid :

- heat

**10.5. Incompatible materials**

Keep away from :

- oxidising agents

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

Repeated or prolonged contact with the substance may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

**11.1.1. Substances**

**Acute toxicity :**

LOW VISCOSITY MINERAL OIL

Oral route :

LD50 > 5000 mg/kg

Species : Rat

Dermal route :

LD50 > 3000 mg/kg

Species : Rabbit

**Aspiration hazard :**

May be fatal if swallowed and enters airways.



**LIQUIDE DIAMANTE REF 3 HOUG 10 ET 6 HOUG 10 - 33083-33084**

---

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

---

**SECTION 12 : ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.2. Persistence and degradability**

**12.2.1. Substances**

LOW VISCOSITY MINERAL OIL

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

No data available.

**German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 1 : Slightly hazardous for water.

---

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the substance and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :**

12 01 07 \* mineral-based machining oils free of halogens (except emulsions and solutions)

---

**SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

**14.1. UN number**

-

**14.2. UN proper shipping name**

-

**14.3. Transport hazard class(es)**

-

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

