

IP-FAST

EPOXY RESIN WITH FAST POLYMERIZATION

New cold mounting resin high performance by PRESI.



Controls and analysis times process reduced.



Perfect for a better penetration of the resin into the sample.



VERY LOW SHRINKAGE

Preserves the edges of the sample and reduces the risk of pollution.

EXCELLENT HARDNESS (89 ShD)

Make easier polishing process for better flatness.

TRANSPARENT RESIN

Better visualization of the sample.



THE PRESI SIGNATURE. ALL AROUND THE WORLD.



IP-FAST RESIN

IP-FAST epoxy resin was designed to reduce significantly controls and analysis times of the mounted samples. This transparent resin has an excellent hardness (89 ShD), a very low shrinkage and viscosity. Its big advantage is to **polymerize very quickly** (in 2 hours).

REF.	DESCRIPTION
04070	Pack 1kg IP-FAST resin + 300CC catalyst
04071	Bottle 300CC catalyst IP-FAST resin
04072	Bottle 1KG resin IP-FAST

FOR USE WITH ...

IP-FAST resin can be used with moulds





Teflon

Rubber





Polyethylene

 $KM^{2.0}$

PRESSURE VESSEL



The vessel for mounting under pressure can dramatically improve the quality of mounts : more **transparent** and reduced **shrinkage**.



...and with accessories



Spring clips



Holding clips



Paper cups



Nitrile gloves

PRESI, IT'S ALSO...

CUTTING



EVO 400

MOUNTING



Mecapress 3

POLISHING



Mecatech 334

HARDNESS & MICROSCOPY



HZ50-4 hardness tester

CONSUMABLES



Abrasive discs



